netvox

Wireless Infrared Gateway with 4 External Ports

Wireless Infrared Gateway with 4 External Ports Z211 Data Sheet

Wireless Sensor Network Based on ZigBee Technology



Z211

Copyright©Netvox Technology Co., Ltd.

This document contains proprietary technical information which is the property of NETVOX Technology. It shall be maintained in strict confidence and shall not be disclosed to other parties, in whole or in part, without written permission of NETVOX Technology.

The specifications are subject to change without prior notice.

netvox

Wireless Infrared Gateway with 4 External Ports

General Description

The Z211 is a smart router and high-reliability network router for indoor use. It integrates a chip module that conforms to the ZigBee ProTM wireless protocol and can communicate with routers, coordinators and terminals of the ZigBee network.

The Z211 is a ZigBee device capable of IR IR learning and IR applications. After IR learning, it can directly control electrical devices that can receive IR control, and can receive IR signals from the infrared remote control to directly control ZigBee devices.

Main Characteristics

- Compliant with ZigBee ProTM protocol specifications for ZigBee networks
- Use the 2.4GHz ISM band for a total of 16 channels
- Wireless communication distance is 120 meters (depending on the specific environment)
- Built-in serial communication FLASH memory AT25SF041, 4Mbits capacity
- Infrared receiving and transmitting functions

Electric Parameters

Power Supply	+12V DC adapter
Static Working Current	50mA/12V/0.6W
Infrared Signal Learning Frequency	38KHz
Infrared Signal Control Distance	32 meters

Frequency Parameters

Frequency Range	$2.4 \sim 2.4835 \mathrm{GHz}$
Channel Numbers	16 (ISM 11th to 26th channels)
Data Transfer Rate	250 Kbps
Spread Technique	DSSS (O-QPSK)
TX Power	7dBm
Rx Sensitivity	-101dBm
Antenna Type	Build-in antenna
Communication Rang	210m (line-of-sight)

Physical Parameters

Dimension	D:106mm H:30.6mm
Working Temp.	$-10^{\circ}\text{C} \sim 50^{\circ}\text{C}$
Storage Temp.	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Humidity	<95%RH (No condensation)

netvox

Wireless Infrared Gateway with 4 External Ports

Contact:

NETVOX TECHNOLOGY CO., LTD.

TEL: 886-6-2617641 FAX: 886-6-2656120 E-mail: sales@netvox.com.tw WEB: www.netvox.com.tw

NETVOX TECHNOLOGY CO., LTD (XIAMEN)

TEL: 86-592-5717188 FAX: 86-592-5717180 E-mail: dyx@netvox.com.cn WEB: www.netvox.com.cn